

VONE RRR EVO. WC Team Edition SETTING DATA Ver 1.00

NAME	Team KYOSH0	TEMP	°C	ENGINE		MUFFLER	
DATE	2006/10/05	HUMIDITY	%	HEAD CLEARANCE	mm	FUEL TYPE	
TRACK		TRACTION	%	PLUG No.		RADIO	

CASTER	ANGLE
2mm	8.5°
1mm	10.5°
0mm	12.5°

SHOCK OIL	300 350 400 450 500 550 600 700 800
DIAPHRAGM	N N(W5189-05)
SHOCK PISTON	(N) φ1.1-2HOLE
SPRING	BLUE (VZ242-4517)
SPRING ADJUSTER	mm
SHOCK POSITION	0 1 (1.5) 2 2.5 3
CASTER ANGLE	1 mm
CAMBER ANGLE	L 0 0.5 1 1.5 2 2.5 3 R 0 0.5 1 1.5 2 2.5 3
TOE ANGLE	-1°
FRONT WIDTH	200 mm
UP STOP	- mm
DOWN STOP	0 mm
SERVO SAVER	10 (1) 12
SERVO ANGLE	95%
UPPER ARM POS	0 0 (0) 0
KNUCKLE ARM SPACER	0 mm
KNUCKLE ARM TYPE	(0°) 1° 2°
DIFF/ONE WAY/RIGID	
ANTIROLL BAR	(SOFT)
TIRE HARDNESS	36235-37°
WHEEL OFFSET	(0) 1 2
TYRE DIAMETER	φ 62 mm
CHASSIS HEIGHT	6 mm

GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL	GEAR	TOTAL
15	61	8.13	15	60	8.00	15	59	7.87	20
16	61	7.63	16	60	7.50	16	59	7.38	21
17	61	7.18	17	60	7.06	17	59	6.94	22
									23
									56
									55
									54
									53
									52
									51
									50
									49
									48
									47
									46
									45
									44
									43
									42
									41
									40
									39
									38
									37
									36
									35
									34
									33
									32
									31
									30
									29
									28
									27
									26
									25
									24
									23
									22
									21
									20
									19
									18
									17
									16
									15
									14
									13
									12
									11
									10
									9
									8
									7
									6
									5
									4
									3
									2
									1

SHOCK OIL	300 350 400 450 500 550 600 700 800
DIAPHRAGM	N N(W5189-05)
SHOCK PISTON	(N) φ1.1-2HOLE
SPRING	BLUE (VZ243-5017)
SPRING ADJUSTER	mm
SHOCK POS	0 1 2 (3) 4 5
WHEEL SPACER	(0mm) / 2mm
UPPER ARM HEIGHT	2 mm 1 / 2 / 3 / A (B)
CAMBER ANGLE	L 0 0.5 (1) 1.5 2 2.5 3 3.5 4 R 0 0.5 (1) 1.5 2 2.5 3 3.5 4
TOE ANGLE	+2.5°
REAR WIDTH	200 mm
DOWN STOP	4 mm
ANTIROLL BAR	1.8 (2.0) 2.3 / ADJ
TIRE HARDNESS	36234-37°
WHEEL OFFSET	0 1 (2)
TYRE DIAMETER	φ 64 mm
CHASSIS HEIGHT	7 mm
LOWER ARM POS	0 0 (0) 0
BODY	PROTOFORM DODGE 3.1
BODY POSITION	N mm
WING HEIGHT	N mm
WING ANGLE	N °

FLYWHEEL	N(VS029) (OPT VSW043)	PINION GEAR	15 (16) 17 / 20 (21) 22 23
CLUCH SHOE	N RED (GREY)	SPUR GEAR	59 60 (61) / 55 (56)
CLUTCH WEIGHT	(N)	DRIVE RATIO	0mm Difference (24T PULLEY 387 BELT) 2mm Difference (23) PULLEY 384 BELT
CLUTCH SPRING	FM432 (4D)	BRAKE	NORMAL 60 %
CLEARANCE	0.5 mm	REAR DIFF	#30000
ADJ. NUT	1.2 mm		

MEMO